

Technical and Safety Specification

Silicone nurse watch REF: 24 300 40-41-45-46-47-48-49-51-52-60-62-65 24 303 00

TCE3

Created on: **27.11.2012**

Updated: 28.01.2016

Index: c Page 1/1

General description		rse brooch fob watch. is not a medical device within the meaning of Directive 93/42/EEC
Attachments	No	
Batch reference	No	
Connected device	No	Watch with silicone case
Single use device	No	
Sterile device	No	
Sterilisation	No	
Autoclavable	No	
Cleaning	Yes	Remove the watch from its silicone case and clean the silicone part with a cloth, using soapy water or 70% alcohol. For the watch itself, use a damp cloth (watch is waterproof).
Component parts	Yes	Watch with silicone case
Material	Silicone, metal, plastics, and glass watch crystal.	
Contains latex	No	
Directive	2004/108/EC and 2002/95/EC	
Standard	Complies with standards: EN 61000-6-1: 2001 and EN 61000-6-3: 2001 + A11: 2004	
Labelling	No	
Packaging	Yes	Metal case, bag, and small cardboard box. Protective foam inside.
Special packaging	No	
Duration of use	Continuous	
Marking on device	Yes	Comed logo
References + extensions		24 300 40-41-45-46-47-48-49-51-52-60-62-65 / 24 303 00
Designation		Silicone nurse watch
Dimensions L x W (mm)		85 x 40
Thickness (mm)		10
Crystal ø (mm)		25
Net weight (g)+1%		28
Battery		SR626SW button cell
Colours		40 = White; 41 = Blue; 45 = Black; 46 = Pink; 47 = Green; 48 = Purple; 49 = Red; 51 = Yellow; 42 = Orange; 60 = Zebra; 62 = Flowers; 65 = Leopard; 24 303 00 = white, blue, pink kit
Temperature resistance (°C	. ()	-20° to + 50°C
Usage		For reading the time and noting beats per minute.
Instruction for use		To start the watch, detach it from its silicone case and remove the protective tab on the winder. Pull the winder and turn it to select the time, then push the winder back in to set. Replace the watch in the opposite side to the brooch fastener. Changing the battery: On the back of the watch there is a groove that allows the battery case to be opened. Lift the back part up with a thin, pointed object. Lift the white plastic cover and remove the battery by sliding it onto its side. Insert the new battery with the correct polarity

Editor: Marion KLEIN

Role: QA Initials: MK COMED sas 8 Rue Louise Michel 67200 STRASBOURG France www.comed.fr



Technical and Safety Specification

Silicone nurse watch REF: 24 300 40-41-45-46-47-48-49-51-52-60-62-65

24 303 00 TCE3

Created on: **27.11.2012**

Updated: 28.01.2016

Index: c Page 2/2

	Be careful not to pierce yourself with the brooch pin. Do not leave exposed
Precautions for use and/or single use warning	to the sun. You may notice that one of the hands moves loosely before the watch has been started. This is because the watch has not yet been activated. Once the protective tab has been removed, the hand will only be
	able to move in one direction.
Recycling	Yes
	Through an approved waste disposal company or your COMED distributor /
Recovery	Yes for the battery, via a used battery collector through your distributor.
	Also see the BATTERIES procedure at www.comed.fr
WEEE/REACH	Yes see WEEE procedure at www.comed.fr/ (SR626SW button) / Yes see
WLLL/ NLACI I	BATTERIES
Safety data	Hazard symbols = none S- and R-phrases = none

Editor: Marion KLEIN

Role: QA Initials: MK COMED sas 8 Rue Louise Michel 67200 STRASBOURG France www.comed.fr