



HKN-93 SERIES

INFANT RADIANT WARMER



Stock code [300314]



Brief Introduction

- Three control Modes: Pre-warm Mode, Manual Mode and Baby Mode control by micro-computer;
- Set Temperature and Baby Temperature can be displayed separately;
- Horizontal angle of warmer module and inclination of the bassinet can be adjusted;
- The panels surrounded bassinet can be turned outward or disassembled;
- X-ray cassette under the bassinet;
- APGAR timer;
- Multiple failure alarm indications;
- RS232 connector for data output.

Specification

Power requirement:

AC220V-230V/50Hz or AC110-120V/50-60Hz, 700VA (HKN-93)

AC220V-230V/50Hz or AC110-120V/50-60Hz, 750VA (HKN-93B / 93A)

Control Mode: Pre-warm Mode, Manual Mode and Baby Mode are controlled by micro-computer

Baby Mode temperature control range: 34.5°C-37.5°C

Skin temperature display range: 5°C-65°C

Accuracy of skin temperature sensor: $\pm 0.2^{\circ}\text{C}$

Temperature uniformity of mattress: $\leq 2^{\circ}\text{C}$

Angle of heater head: 0°, 30°, 60°, 90° for two ways

Inclination of the bassinet: $\pm 10^{\circ}$

APGAR timer: audible and visible alarm when the device runs to 50" ~ 1' , 4' 50" ~ 5' , 9' 50" ~ 10'

Failure alarm: over temperature alarm, deviation alarm, sensor failure alarm, power failure alarm, setting alarm, checking alarm and so on.

The total irradiance Ebi on the effective surface area:

$\geq 0.66\text{mW}/\text{cm}^2$ (HKN-93B / 93A)

Average value of general bilirubin radiation on the mattress effective range: $\geq 0.58\text{mW}/\text{cm}^2$ (HKN-93B / 93A)

Bilirubin uniformity of radiating on the mattress effective range:

> 0.4 (HKN-93B / 93A)

Dominant wavelength of blue light: 420-470nm

Optional Configuration

Disposable skin temperature sensor, Vertical height adjustment (VHA) stand, Weighing system and SpO₂.

Standard Configuration

HKN-93:

Warmer module, bassinet, main column, mobile stand, controller, I.V. Pole and tray.

HKN-93B:

Based on HKN-93, plus the phototherapy unit.

HKN-93A:

Based on HKN-93B, plus the breath resuscitation bag, infant head fixing unit, the oxygen supplying set (the oxygen cylinders, buoy type oxygen regulator, wall type oxygen regulator), low-pressure suction.

Environmental Requirement

Operating range: 18°C-30°C

Ambient air velocity rate: < 0.3 m/s

Product Packaging

Package: The whole unit is packed into one carton

Dimension: 1270mm x 810mm x 1120mm

Gross Weight: 110kg(HKN-93)

120kg(HKN-93B)

142kg(HKN-93A)



HKN-93



HKN-93B



HKN-93A



Ningbo David Medical Device Co.,Ltd

Add: Bldg No. 5 Ningbo Smart Park, #98 Chuangyuan Rd, Hi-tech Zone, Ningbo, China

Tel: 0086-574-8780 0008 or 8780 0007

/Fax: 0086-574-8780 3714

E-mail: sales@nbdavid.com

/Web.: www.nbdavid.com

/P.C.: 315048