



Boaray 3000D Ventilator

- 20-2000ml (VCV); Applicable to adult, pediatric and infant
- Various ventilation modes for different needs of all patients
- 10.1 inch TFT screen with big font view for easy observation
- Touch screen (optional)
- Navigation knob for simple operation
- Simultaneous display of 3 waveforms and 2 loops
- Synchronized nebulizer (optional)
- Low noise and water-free medical air compressor (optional)
- Expiratory valve could be taken off for autoclavable disinfection to avoid cross-infection
- Active exhalation valve with anti condensation design
- World leading brands of key components of ventilator ensure high accuracy and stable performance
- Advanced proportional solenoid technology to realize accurate ventilation control
- Multi-safety mechanism and three-priority alarm of visual and audio for different risks

Specification	Boaray3000D
Patient type:	Adult, Pediatric and infant ($\geq 5\text{kg}$)
Ventilation modes:	VCV, PCV, SIMV(V)+PS, SIMV(P)+PS, SPONT/CPAP, Sigh, Standby Optional: PRVC, DualPAP, NPPV
Tidal Volume:	20-2000 mL
Ventilation frequency:	1-100 bpm
Inspiration time:	0.1-10 S (increment:0.1S)
FiO ₂ :	21%-100%
Flow trigger:	0.5-20L/Min
Pressure trigger:	-20-0cmH ₂ O
Pressure control:	5-70 cmH ₂ O
Pressure support:	0-70 cmH ₂ O
Electronic PEEP:	0-50 cm H ₂ O (increment:1 cm H ₂ O)
Nebulizer (optional):	30 minutes
Direct access function:	Freeze, Lock
Monitoring:	Volume:V _{TI} , V _{TEf} , MV, MVspont. Pressure:Ppeak, Pmean, Pplat, Pmin, PEEP,Freq, Fspont, I:E, FiO _{2f} , Compliance, Resistance, RSB, P0.1, NIF, Auto PEEP, Rcxp,Cdyn
Waveform:	P-T, F-T, V-T
Loop:	P-V, F-V, F-P
Trend:	Peak, FiO _{2f} , PEEP, MV, V _{TEf} , V _{TI}
System Log:	500 events (setting and alarm)
Alarm:	Audio and visual alarms with three levels Volumes: V _{TE} high/low, MV high/low; Pressure: Paw high/low O ₂ supply pressure high/low, Air supply pressure high/low Apnea, Continuous high airway pressure Freq high/low, FiO ₂ high/low Power: AC power failure, Low battery power, Exhausted battery failure

Physical Specification	
Dimensions (H×W×D):	Host:631*725*605(mm) Trolley:225*805*555(mm)
Communication Interface:	RS232
Screen:	10.1 inch TFT Screen
Net weight:	Host:42kg,Trolley:22.5kg
Power:	100-240VAC, 50/60Hz, 1A(Max)
Lithium Battery:	Minimum 120 minutes

Shenzhen PRUNUS Medical Co., Ltd.

9th Floor, Prunus Building, Block C, Funing High-Tech Industrial Zone,
No.71 Xintian Road, Baoan District, Shenzhen, Guangdong,
P.R.China

Tel: +86 755 2689 9781

Fax: +86 755 2689 9789

E-mail: international@prunusmedical.com

Web: www.prunusmedical.com